INDOOR AIR QUALITY METER

Measures CO₂, Temperature and Humidity



[33,36] 8-1/4 [209.44] 6-3/4 [171.34] @ *6*

The Model AQH-20 Handheld Indoor Air Quality Meter reduces the number of instruments a contractor has to carry by measuring carbon dioxide concentration. air temperature, and humidity percentage in one device. A large backlit LCD shows all three parameters simultaneously. This product offers user selectable engineering units, maximum/minimum/average readings, a hold function, and an audible alarm.

FEATURES/BENEFITS

- All-in-one unit for carbon dioxide, temperature, and humidity
- Large backlit LCD for visibility in dark areas
- · User configurable alarms for audible indication of hazardous conditions

APPLICATIONS

- · Building commissioning
- · Green house monitoring

MODEL CHART			
Model	CO ₂ Range	Humidity Range	Temperature Range
AQH-20	0 to 2000 ppm	0.0 to 99.9%	14 to 140°F (-10 to 60°C)

SPECIFICATIONS

Ranges: CO2: 0 to 2000 ppm; Temperature: 14 to 140°F (-10 to 60°C): Relative Humidity: 0.0 to 99.9% RH. Accuracy: CO2: ±30 ppm ±5% of reading: Temperature: ±0.9°F (±0.6°C):

Humidity: ±3% RH (10 to 90%), ±5% (0.0 | Humidity Limits (Non-Condensing); 0 to 9.9% or 90 to 99.9%).

Resolution: CO₂: 1 ppm: Temperature: 0.1°F (0.1°C): Humidity: 0.1% RH. Response Time: CO2: < 30 s;

Temperature: < 2 minutes: Humidity: < 10 minutes.

Display: 4 digits for temperature/CO2 and 3 digits for humidity.

2-11/64 [55.07]

1-5/16

CO₂ Sensor: Non-dispersive infrared. Temperature Limits: 32 to 122°F (0 to 50°C)

to 95% RH.

Power Requirements: (4) 1.5 V AA alkaline batteries, included, user replaceable.

Warm Up Time: 30 s. Weight: 6.76 oz (200 a).

ACCESSORIES				
Model	Description			
TH-CAL	33% and 75% salt bath calibration standards			