

## MODEL LOVELINK™III

## CONFIGURATION MONITORING &amp; LOGGING SOFTWARE

Designed for Love Temperature Controls



**MODEL LOVELINK™III** Configuration, Monitoring and Logging Software is an easy to use program allowing connection of up to 40 controls on a single computer port. Data logging can be set up by individual control with varying logging parameters.

**FEATURES/BENEFITS**

- Address and store data for up to 40 controls
- Data logging at individually adjustable rates
- On-screen graphing for up to 10 zones
- Upload and download control configuration profiles
- Save and retrieve control configuration profiles

**APPLICATIONS**

- Oven, boiler, or chiller control
- Hot plates/melt pots
- Packaging equipment
- Environmental chambers
- Medical equipment
- Food service equipment

**COMPUTER REQUIREMENTS**

The LoveLink™III software application will run on Windows® 2000 and Windows® XP Software. One available RS-232 or RS-485 port is needed to communicate with the temperature control(s). A minimum of 4 MB of hard disk space is needed for the LoveLink™III software application files, and additional hard disk space is needed to store temperature log files. Log file size will vary depending on the Duration and Rate selected for the controls and the number of controls on line.

**CONTROL REQUIREMENTS**

The temperature controls supported by LoveLink™III software are the Love 4B, 4C, 2600, 8B, 8C, 8600, 16A, 16B, 16C, 16L, 32A, 32B, 32DZ, SCD and SCZ Series.

**MODEL CHART**

Model

LOVELINK III

**ACCESSORIES**

Model Description

MN-1 Mini-Node™ USB/RS-485 converter

Windows® is a registered trademark of Microsoft Corporation  
Windows NT® is a registered trademark of Microsoft Corporation